

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD SHINGLE PROHIBITED)

METAL BIRDSTOP OR 36"
WIDE 72 # MINERAL-
SURFACED NONPERFORATED
CAP SHEET (ASTM D3909)

G.I. FLASHING

1x STOP

2x CONTINOUS

2x FRAMING

7/8" STUCCO
MINIMUM

STUCCO OPTION 1

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD
SHINGLE PROHIBITED)

METAL BIRDSTOP OR 36"
WIDE 72 # MINERAL-
SURFACED NONPERFORATED
CAP SHEET (ASTM D3909)

G.I. FLASHING

2x CONTINOUS

7/8" STUCCO MINIMUM

STUCCO OPTION 2

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD
SHINGLE PROHIBITED)

METAL BIRDSTOP OR 36" WIDE
72 # MINERAL-SURFACED
NONPERFORATED CAP SHEET
(ASTM D3909)

G.I. FLASHING

2 x CONTINOUS

7/8" STUCCO MINIMUM

STUCCO OPTION 3

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD
SHIGNLE PROHIBITED)

METAL BIRDSTOP OR 36" WIDE
72 # MINERAL-SURFACED
NONPERFORATED CAP SHEET
(ASTM D3909)

G.I. FLASHING

2 x CONTINOUS

7/8" STUCCO MINIMUM

STUCCO OPTION 3

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD
SHINGLE PROHIBITED)

METAL BIRDSTOP OR 36"
WIDE 72 # MINERAL-
SURFACED NONPERFORATED
CAP SHEET (ASTM D3909)

G.I. FLASHING

2x CONTINOUS

RATED FIBER CEMENT SIDING
INSTALLATION PER MANUFACTURER

1/2" STRUCTURURAL PLYWOOD PANELS
(EXTERIOR GLUE) OR 5/8" TYPE X

FIBER CEMENT OPTION 1

CLASS A ROOF COVERING
(WOOD SHAKE OR WOOD
SHIGNLE PROHIBITED)

METAL BIRDSTOP OR 36" WIDE
72 # MINERAL-SURFACED
NONPERFORATED CAP SHEET
(ASTM D3909)

G.I. FLASHING

2 x CONTINOUS

RATED FIBER CEMENT SIDING
INSTALLATION PER MANUFACTURER

1/2" STRUCTURAL PLYWOOD PANELS
(EXTERIOR GLUE) OR 5/8" TYPE X

FIBER CEMENT OPTION 2